

MAY 14 2003



U.S. Department
of Transportation
**Research and
Special Programs
Administration**

400 Seventh St., S.W.
Washington, D.C. 20590

DOT-E 6071
(SEVENTH REVISION)

EXPIRATION DATE: April 30, 2005

(FOR RENEWAL, SEE 49 CFR § 107.109)

1. GRANTEE: Kidde Aerospace
Wilson, NC
2. PURPOSE AND LIMITATION:
 - a. This exemption authorizes the manufacture, mark, sale and use of a non-DOT specification cylinder conforming to all regulations applicable to DOT Specification 4DA, except as specified herein, for use in transporting materials authorized under this exemption. This exemption provides no relief from the Hazardous Materials Regulations (HMR) other than as specifically stated herein.
 - b. The safety analyses performed in development of this exemption only considered the hazards and risks associated with transportation in commerce. The safety analyses did not consider the hazards and risks associated with consumer use, use as a component of a transport vehicle or other device, or other uses not associated with transportation in commerce.
3. REGULATORY SYSTEM AFFECTED: 49 CFR Parts 106, 107 and 171-180.
4. REGULATIONS FROM WHICH EXEMPTED: 49 CFR §§ 173.302a, 173.304a, 173.305 and 175.3 in that non-DOT specification cylinders are not authorized, except as specified herein.
5. BASIS: This exemption is based on the application of Kidde Aerospace dated April 7, 2003, submitted in accordance with § 107.109.

MAY 14 2003

6. HAZARDOUS MATERIALS (49 CFR § 172.101):

Proper Shipping Name/ Hazardous Materials Description	Hazard Class/ Division	Identi- fication Number	Packing Group
Compressed gas, n.o.s. (Mixture of bromotrifluoromethane and nitrogen)	2.2	UN1956	N/A

7. SAFETY CONTROL MEASURES:

a. PACKAGING - Prescribed packaging is a non-DOT specification stainless steel pressure vessel complying with DOT Specification 4DA (§§ 178.35 and 178.58) except as follows:

§ 178.35(e) *Safety devices*

Applies except the maximum operating pressure for the safety relief device is at least 100 psig below the pressure of required for the hydrostatic test under § 178.58(i).

§ 178.35(f) *Markings*

Applies except the exemption number must be marked in lieu of "DOT-4DA."

§ 178.58(a) *Type, size and service pressure*

The container capacity must not exceed 2500 cubic inches with a maximum service pressure of 1,000 psig.

§ 178.58(b) *Steel*

The authorized material of construction is a stainless steel designated Almar-362, product of the Allegheny-Ludlum Company.

§ 178.58(f) *Wall thickness*

Wall thickness calculations shall be based on the data submitted in the Walter Kidde and Company, Incorporated's petition of June 6, 1969.

MAY 14 2003

§ 178.58(g) *Heat treatment*

Paragraphs (1), (3), and (4) do not apply.

§ 178.58(i) *Hydrostatic test*

Applies except that each container must be tested to at least 2.50 times the service pressure.

§ 178.58(j) *Burst test*

The minimum burst pressure must be 1.33 times the hydrostatic test pressure as specified in § 178.58(i).

b. TESTING - Pressure vessels are subject to the retest requirements applicable to DOT-4DA containers prescribed in § 180.209.

c. OPERATIONAL CONTROLS - Pressure in the vessel must not exceed 800 psig at 70°F. The filling limits of § 173.301a(a) and § 173.305(b) apply.

8. SPECIAL PROVISIONS:

a. In accordance with the provisions of Paragraph (b) of § 173.22a, persons may use the packaging authorized by this exemption for the transportation of the hazardous materials specified in paragraph 6, only in conformance with the terms of this exemption.

b. A person who is not a holder of this exemption, but receives a package covered by this exemption, may reoffer it for transportation provided no modification or change is made to the package or its contents and it is offered for transportation in conformance with this exemption and the HMR.

c. A current copy of this exemption must be maintained at each facility where the package is offered or reoffered for transportation.

d. Each packaging manufactured under the authority of this exemption must be marked with a registration symbol designated by the Office of Hazardous Materials Exemptions and Approvals for a specific manufacturing facility.

MAY 14 2003


- e. A current copy of this exemption must be maintained at each facility where the package is manufactured under this exemption. It must be made available to a DOT representative upon request.
- f. The cylinder must be shipped in strong outside packagings in accordance with § 173.301(a)(9).
- g. Transportation of oxygen is only authorized in aircraft when in accordance with § 172.102(c)(2) Special Provision A52 and §§ 175.85(h) and (i).
- h. MARKING - Packages specified herein marked "DOT SP 6071" prior to the issuance of this exemption may be transported under the terms of this exemption.
9. MODES OF TRANSPORTATION AUTHORIZED: Motor vehicle, rail freight, cargo aircraft only, and passenger-carrying aircraft.
10. MODAL REQUIREMENTS: A current copy of this exemption must be carried aboard each aircraft used to transport packages covered by this exemption. The shipper must furnish a copy of this exemption to the air carrier before or at the time the shipment is tendered.
11. COMPLIANCE: Failure by a person to comply with any of the following may result in suspension or revocation of this exemption and penalties prescribed by the Federal hazardous materials transportation law, 49 U.S.C. 5101 et seq:
- o All terms and conditions prescribed in this exemption and the Hazardous Materials Regulations, 49 CFR Parts 171-180.
 - o Registration required by § 107.601 et seq., when applicable.

Each "Hazmat employee", as defined in § 171.8, who performs a function subject to this exemption must receive training on the requirements and conditions of this exemption in addition to the training required by §§ 172.700 through 172.704.

No person may use or apply this exemption, including display of its number, when the exemption has expired or is otherwise no longer in effect.

12. REPORTING REQUIREMENTS: The carrier is required to report any incident involving loss of packaging contents or packaging failure to the Associate Administrator for Hazardous Materials Safety (AAHMS) as soon as practicable. (Sections 171.15 and 171.16 apply to any activity undertaken under the authority of this exemption.) In addition, the holder(s) of this exemption must inform the AAHMS, in writing, of any incident involving the package and shipments made under the terms of this exemption.

Issued in Washington, D.C.:



for Robert A. McFaire
Associate Administrator for
Hazardous Materials Safety

MAY 14 2003

(DATE)

Address all inquiries to: Associate Administrator for Hazardous Materials Safety, Research and Special Programs Administration, Department of Transportation, Washington, D.C. 20590.
Attention: DHM-31.

Copies of this exemption may be obtained by accessing the Hazardous Materials Safety Homepage at <http://hazmat.dot.gov/exemptions> Photo reproductions and legible reductions of this exemption are permitted. Any alteration of this exemption is prohibited.

PO: KFW/alb