



U.S. Department
of Transportation
**Research and
Special Programs
Administration**

400 Seventh St., S.W.
Washington, D.C. 20590

SEP 22 2003

DOT-E 12290
(SECOND REVISION)

EXPIRATION DATE: July 31, 2005

(FOR RENEWAL, SEE 49 CFR § 107.109.)

1. GRANTEE: Savage Services Corporation
Pottstown, PA
(Former grantee:Savage Industries, Incorporated)
2. PURPOSE AND LIMITATION:
 - a. This exemption authorizes the loading of tank cars, coupled in a series with the bottom discharge outlet caps in place on all cars except the first and last, with the setting of the hand brake and the blocking of a wheel, in both directions, on the first and last cars of a series of coupled tank cars, prior to unloading. This exemption provides no relief from any Hazardous Materials Regulation (HMR) other than as specially stated herein.
 - b. The safety analyses performed in development of this exemption only considered the hazards and risks associated with transportation in commerce.
3. REGULATORY SYSTEM AFFECTED: 49 CFR Parts 106, 107 and 171-180.
4. REGULATIONS FROM WHICH EXEMPTED: 49 CFR § 172.302(c) in that marking the exemption number on tank cars is waived; and § 174.67 (a) (2).
5. BASIS: This exemption is based on the application of Savage Industries, Incorporated, dated August 11, 2003, submitted in accordance with § 107.109 and supplemental information dated August 28, 2003 and supplemental information date September 19, 2003.

6. HAZARDOUS MATERIALS (49 CFR 172.101):

SEP 22 2003

Hazardous Materials Description			
Proper Shipping Name	Hazard Class/ Division	Identi- fication Number	Packing Group
Acetone	3	UN 1090	II
Acetic acid, glacial or Acetic acid solution, with more than 80 percent acid, by mass.	8	UN 2789	II
Bisulfites, inorganic, aqueous solution, n.o.s.	8	UN 2963	III
Butyl acetates	3	UN 1123	II
Carbon dioxide, refrigerated liquid	2.2	UN 2187	N/A
Combustible liquid, n.o.s.	Combustible	NA 1993	III
Corrosive liquid, n.o.s.	8	UN 1760	I
Diesel fuel	3	NA 1993	II
Elevated temperature material, liquid, n.o.s., at or above 100 C and below its flash point (including molten metals, molten salts, etc.)	9	UN3257	III
Environmentally hazardous substance, liquid, n.o.s.	9	UN 3082	III
Ethyl methyl ketone or Methyl ethyl ketone	3	UN 1193	II
Ferric chloride solution	8	UN 2582	III
Ferrous chloride solution	8	NA 1760	II
Flammable liquid n.o.s.	3	UN 1993	I
Fluorosilicic acid	8	UN 1778	II
Fuel, aviation, turbine engine	3	UN 1863	III

Hazardous Materials Description			
Proper Shipping Name	Hazard Class/ Division	Identification Number	Packing Group
Fuel oil (No. 1, 2, 4, 5, or 6)	3	NA 1993	III
Gasoline	3	UN 1203	II
Hazardous waste, liquid, n.o.s.	9	NA 3082	III
Heptanes	3	UN 1206	II
Hexanes	3	UN 1208	II
Hydrochloric acid	8	UN 1789	II
Hydrogen peroxide, aqueous solutions, stabilized with more than 60 percent hydrogen peroxide	5.1	UN 2015	II
Isopropanol or Isopropyl alcohol	3	UN 1219	III
Petroleum distillates, n.o.s. or Petroleum products, n.o.s.	3	UN 1268	III
Petroleum gases, liquefied or Liquefied petroleum gas	2.1	UN 1075	
Petroleum oil	3	NA 1270	III
Phosphoric acid, liquid or solid	8	UN 1805	III
Potassium hydroxide, solution	8	UN 1814	II
Sodium hydroxide solution	8	UN 1824	II
Sulfur, molten	9	NA 2448	III
Sulfuric acid with more than 51 percent acid	8	UN 1830	II
Toluene	3	UN 1294	II
Toluene diisocyanate	6.1	UN 2078	II
Waste combustible liquids, n.o.s.	Combustible	NA 1993	III

Hazardous Materials Description			
Proper Shipping Name	Hazard Class/ Division	Identification Number	Packing Group
Xylenes	3	UN 1307	II

7. SAFETY CONTROL MEASURES:

- a. PACKAGING - Packaging prescribed are DOT Specification and non-DOT Specification tank cars authorized by the HMR for the products indicated above. Packages must be equipped with efficient hand brakes which must comply with the Railroad Safety Appliance standards in 49 CFR Part 231.
- b. MARKING - The marking requirement in § 172.302(c) is waived.

8. SPECIAL PROVISIONS:

- a. On a series of coupled cars, the bottom discharge outlet valve caps of the first and last tank cars must be removed when loading.
- b. The bottom discharge outlet valve assembly of each tank car operating under this exemption must be visually inspected every fifteen (15) trips or at a minimum quarterly.
- c. The hand brake must be set and at least one wheel blocked in both directions on the first and last car provided the grade of the track is less than or equal to 0.5 percent.
- d. For grades exceeding 0.5 percent, the following table must be used to determine the percentage of additional hand brakes to be applied:

Grade percent	Percentage of cars to have hand brakes applied
<0 . 5	0
> 0.5 ≤0.6	20
>0.6≤0.7	35
>0.7≤0.8	50
>0.8≤0.9	65
>0.9≤1.0	80
>1.0	100

9. MODES OF TRANSPORTATION AUTHORIZED: Rail freight.
10. MODAL REQUIREMENTS: The Federal Railroad Administration is to be notified if any unusual incident such as derailment or exterior tank car damage occurring from movement by contacting the:
- Federal Railroad Administration
Hazardous Materials Division
RRS-12, Mail Stop 25
1120 Vermont Avenue, N.W.
Washington, D.C. 20590
(202) 439-6229 or 493-6248
11. COMPLIANCE: Failure by a person to comply with any of the following may result in suspension or revocation of this exemption and penalties prescribed by the Federal hazardous materials transportation law, 49 U.S.C Section 5101 et seq:
- All terms and conditions prescribed in this exemption and the Hazardous Materials Regulations, 49 CFR Parts 171-180.

SEP 22 2003


- Registration required by § 107.601 et seq., when applicable.

Each "Hazmat employee", as defined in § 171.8 who performs a function subject to this exemption must receive training on the requirement and conditions of this exemption in addition to the training required by §§ 172.700 through 172.704.

No person may use or apply this exemption, including display of its number, when the exemption has expired or is otherwise no longer in effect.

12. REPORTING REQUIREMENTS: The carrier is required to report any incident involving loss of packaging contents or packaging failure to the Associate Administrator for Hazardous Materials Safety (AAHMS) as soon as practicable. (§§ 171.15 and 171.16 apply to any activity undertaken under the authority of this exemption.) In addition, the holder(s) of this exemption must inform the AAHMS, in writing, of any incident involving the package and shipments made under the terms of this exemption.

Issued in Washington, D.C.:



Robert A. McGuire
Associate Administrator for
Hazardous Materials Safety

SEP 22 2003

(Date)

Address all inquiries to: Associate Administrator for Hazardous Materials Safety, Research and Special Programs Administration, Department of Transportation, Washington, D.C. 20590.
Attention: DHM-31.

Copies of this exemption may be obtained by accessing the Hazardous Materials Safety Homepage at <http://hazmat.dot.gov/exemptions> Photo reproductions and legible reductions of this exemption are permitted. Any alteration of this exemption is prohibited.

PO: WS/sln