



U.S. Department
of Transportation

400 Seventh Street, S.W.
Washington, D.C. 20590

**Research and
Special Programs
Administration**

AUG 25 2004

DOT-E 13488

EXPIRATION DATE: June 30, 2006

(FOR RENEWAL, SEE 49 CFR § 107.109)

1. GRANTEE: FABER INDUSTRIE SPA
Udine, Italy
(U.S. Agent: Kaplan Industries, Maple Shade, NJ)
2. PURPOSE AND LIMITATION:
 - a. This exemption authorizes the manufacture, marking, sale and use of a non-DOT specification cylinder conforming in part with the DOT-3AA specification, for use in the transportation of certain nonflammable, non-liquefied compressed gases transportation in commerce. This exemption provides no relief from the Hazardous Materials Regulations (HMR) other than as specifically stated herein.
 - b. The safety analyses performed in development of this exemption only considered the hazards and risks associated with transportation in commerce.
3. REGULATORY SYSTEM AFFECTED: 49 CFR Parts 106, 107 and 171-180.
4. REGULATIONS FROM WHICH EXEMPTED: 49 CFR §§ 173.301(a)(1), 173.301(a)(2) and 173.302a(a)(1) in that non-DOT specification cylinders are not authorized except as prescribed herein.
5. BASIS: This exemption is based on the application of Faber Industrie dated January 28, 2004 and additional information dated June 25, 2004 submitted, in accordance with § 107.105 and the public proceeding therein.

AUG 25 2004

6. HAZARDOUS MATERIALS (49 CFR § 172.101):

Hazardous Material Description			
Proper Shipping Name	Hazard Class/Division	Identification Number	Packing Group
Nonflammable, non-liquefied gases authorized for DOT 3AA specification cylinders	2.2	as appropriate	n/a

7. SAFETY CONTROL MEASURES:

a. PACKAGING - Packaging prescribed is a high strength, non-DOT specification steel cylinder, conforming with FABER's drawings listed in Table A dated September 08, 2003 on file with the Office of Hazardous Materials Exemptions and Approvals (OHMEA), and DOT specification 3AA (§§ 178.35 and 178.37), except as follows:

§ 178.35(c) *Duties of Inspector.*

* * *

(Add) (5) Verify that the design qualification tests prescribed in § 178.37(d)(3) have been performed with satisfactory results.

(Add) (6) Lot definition. In this exemption, a "lot" means a group of cylinders successively produced and having the same:

- (i) Size and configuration;
- (ii) Specified material of construction;
- (iii) Process of manufacture and heat treatment;
- (iv) Equipment of manufacture and heat treatment;
- (v) Conditions of time, temperature and atmosphere during heat treatment.

AUG 25 2004

In no case may the lot size exceed 200 cylinders, but any cylinder processed for use in the required destructive testing need not be counted as being one of the 200.

§ 178.35(e) *Pressure relief devices and protection for valves and pressure relief devices.*

(Add) Pressure relief devices must be in compliance with § 173.302a(b)(1).

§ 178.35(f) *Marking.*

Applies except that "DOT-E 13488" must replace "DOT-3AA" followed by the service pressure. Test pressure (e.g. "TP 5250") must be marked following or near the service pressure. The letters "TP" preceding the test pressure is optional.

§ 178.35(g) *Inspector's Report.*

The inspector's report must be revised to accommodate the above changes in requirements.

§ 178.37(a) *Type, size and service pressure.*

(1) Seamless cylinder with nominal outside diameter, minimum wall thickness, minimum base thickness maximum, water capacity and service pressure in accordance with Table A.

(2) Does not apply.

§ 178.37(b) *Authorized steel.*

Electric furnace or equivalent steel of uniform quality is authorized. The steel analysis must conform with the following:

AUG 25 2004

CHEMICAL COMPOSITION IN WEIGHT PERCENT

<u>Element</u>	<u>Ladle Analysis</u>	<u>Check Analysis Tolerance</u>	
		<u>Under</u>	<u>Over</u>
Carbon	0.32/0.37	0.01	0.01
Manganese	0.60/0.90	0.03	0.03
Phosphorus	0.015 max.	-	0.01
Sulfur	0.010 max.	-	0.00
Silicon	0.15/0.35	0.02	0.03
Chromium	0.90/1.15	0.03	0.03
Molybdenum	0.15/0.25	0.01	0.01
Nickel	0.25 max.	0.01	0.00
Aluminum	0.015/0.05	-	0.00
Copper	0.25 max.	-	0.00
Sulphur plus - phosphorus	0.25 max.	-	0.00

Note 1: Steel shall be treated with calcium to provide the following J-K microcleanliness rating per ASTM Standard E-45, Method.

<u>A (Sulfides)</u>		<u>B (Alumina)</u>		<u>C (Silicates)</u>		<u>D (Oxides)</u>	
<u>Thin</u>	<u>Heavy</u>	<u>Thin</u>	<u>Heavy</u>	<u>Thin</u>	<u>Heavy</u>	<u>Thin</u>	<u>Heavy</u>
2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0

Certificate from the material manufacturer must certify that the material was calcium treated and must include in such certification the J-K microcleanliness rating for each heat of steel.

Note 2: Steel shall be aluminum killed and made by a fine grained de-oxidation practice.

§ 178.37(c) *Identification of material.*

Materials must be identified by any suitable method. Steel stamping of heat identification must not be made in any area that will eventually become the sidewall of the cylinder. Depth of stamping shall not encroach upon the minimum prescribed wall thickness of the cylinder.

AUG 25 2004

§ 178.37(d) *Manufacture.*

(1) Cylinder shells must be of seamless construction manufactured by the deep drawing method with integrally formed heads and bottoms; dirt and scale to be removed as necessary to afford proper inspection; no fissure or other defect acceptable that is likely to weaken the finished cylinder appreciably. The general surface finish shall not exceed a roughness of 250 r.m.s. individual irregularities such as draw marks, scratches, pits, etc. should be held to a minimum. If the cylinder is not originally free of such defects or does not meet the finish requirements, the surface may be machined or otherwise treated to eliminate these defects. Metal removal for any purpose other than removal of isolated defects and threading must be done prior to the hydrostatic test. The thickness of the treated areas must be measured and must not be less than the minimum prescribed thickness. Cylinder end contour must be hemispherical or ellipsoidal (axis ratio of 2:1) with concave side to pressure.

(2) Shape and thickness of the cylinder bottom and sidewall adjacent to the bottom must be such that failure during the cycle pressure test occurs in the sidewall of the cylinder. The thickness of the cylinder bottom must be no less than the cylinder sidewall thickness.

(3) Design qualifications: The design authorized herein and any significant change to this design must be qualified for production by performing the test specified below:

(i) Burst Test. Three cylinders must be hydrostatically burst without evidence of fragmentation. The rate of pressurization must not exceed 200 psi per second. Cylinders subjected to the burst test must withstand a pressure of at least 2.25 times the service pressure without failure. Failure must initiate in the sidewall in a longitudinal direction, and the cylinder must remain in one piece.

(ii) Flattening Test. Three cylinders must be flattened to eight times the wall thickness without cracking.

AUG 25 2004

(iii) Cycle Test. Three cylinders must be cycle tested to destruction to an upper cyclic pressure of 1.5 times service pressure. The successive hydrostatic pressurizations from the lower cyclic pressure to the upper cyclic pressure must not exceed a rate of ten cycles per minute. Adequate recording instrumentation must be provided if equipment is to be left unattended for any period of time. Lower cyclic pressure must not exceed 10 percent of the upper cyclic pressure. Cylinders must withstand at least 10,000 cyclic pressurizations without distortion or failure. The failure must occur in the sidewall and the failure mode must be leak before burst (LBB). At least one cylinder must be cycled using water as the pressurizing medium.

(iv) Flawed Burst Test. One cylinder must be cycle tested to destruction at a pressure of 1.25 times the service pressure. This test must be performed after three flaws (slots) are machined into the upper sidewall of the cylinder. The flaws must have a minimum length of $6t$, minimum depth of $0.1t$ and be located at 120° intervals. The flaws must be introduced into the cylinder by a means that will not affect the mechanical or metallurgical properties of the cylinder. The failure mode must be LBB. Examination of the failed cylinder must show evidence of fatigue crack propagation prior to leakage.

In this exemption, "significant change" means a 10 percent or greater change in cylinder wall thickness, service pressure, or diameter; a 30 percent or greater change in water capacity of base thickness; any change in material; over a 100 percent increase in size of openings; or any change in the number openings.

§ 178.37(e) *Welding or brazing*.

Welding or brazing for any purpose is prohibited.

§ 178.37(f) *Wall thickness*.

(1) Does not apply.

AUG 25 2004

(2) The minimum wall thickness must be such that the wall stress at the minimum specified test pressure does not exceed 67 percent of the minimum tensile strength of the steel as determined in § 178.37(f)(2). A wall stress of more than 90,500 psi is not permitted and in no case may the wall thickness be less than that specified in Table A.

(3) Calculation must be made by the formula:

$$S = P(1.3D^2 + 0.4d^2)/(D^2 - d^2)$$

where:

S = wall stress in pounds per square inch;
P = minimum test pressure of 3/2 of service pressure;
D = outside diameter in inches;
d = inside diameter in inches.

§ 178.37(g) *Heat treatment.*

* * *

(1) The completed cylinder must be uniformly heat-treated prior to test.

(2) Each cylinder must be heated and held above the upper critical temperature (Ac_3) for at least one hour per inch of thickness based on the maximum thickness of the cylinder and then quenched in a suitable liquid medium having a cooling rate not in excess of 80 percent of water. The steel temperature on quenching must be above the Ac_3 temperature but not higher than 930 °C.

(3) After quenching, each cylinder must be reheated to a temperature below the transformation range but not less than 540 °C, and must be held at this temperature for at least one hour per inch of thickness based on the maximum thickness of the cylinder. Each cylinder must then be air cooled.

§ 178.37(h) *Openings in cylinders and connections (valves, fuse plugs, etc.) for those openings.*

(1) Threads required, to be clean cut, even, without checks, and to gauge. Openings are permitted in the top head and centerline of the cylinder only.

(2) All openings must be circular and threaded. Straight threads must be used and must conform with the following:

(i) National Gas Straight Thread (NGS) type must conform with the requirements of Federal Standard H-28 (1978), Sections 7 and 9.

(ii) Unified Thread (UN) type must conform with the requirements of Federal Standard H-28 (1978), Section 2.

(iii) Controlled Radius Root Thread (UNJ) type must conform with the requirements of Federal Standard H-28 (1978), Section 4.

(iv) Other straight thread types conforming with ISO standards may be used provided that the requirements of paragraph (3) below are met.

(3) All straight threads must have at least 6 engaged threads, a tight fit, and a factor of safety in shear of at least 10 at the test pressure of the cylinder. Shear stress must be calculated by using the appropriate thread shear area in accordance with Federal Standard H-28 (1978), Appendix A5, Section 3. Gaskets are required to prevent leakage.

§ 178.37(i) *Hydrostatic test.*

* * *

(1) Applies except that water jacket method only is authorized.

(2) * * *

(3) * * *

(4) Each cylinder must be tested to at least 3/2 times marked service pressure.

§ 178.37(j) *Toughness and ductility tests.*

(1) Flattening Test. Between knife edges, wedge-shaped, 60-degree angle, rounded to 1/2 inch radius; test one cylinder taken at random out of each lot of 200 or less cylinders. Longitudinal axis of the cylinder must be at approximately a 90 degree angle to the knife edges.

(2) Impact Tests. For each lot of 200 or less cylinders, three subsize Charpy V-notch specimens must be taken from the lower sidewall of one heat treated test cylinder at approximately evenly spaced (120 degree) intervals and tested at -50 °C in accordance with ASTM E-23.

(3) Flawed Burst Test. For each lot of 200 or less cylinders, one cylinder must be flawed and cycle tested as described in § 178.37(d)(3)(iv) of this exemption.

(4) Hardness examination. A hardness measurement must be performed on the cylindrical section of each cylinder after heat treatment.

§ 178.37(k) *Physical test and magnetic particle examination.*

* * *

(1) * * *

(2) * * *

(i) Specimens must be: Prepared in accordance with ISO 9809-2:1999. Gauge length of 5.65 times S_o , with width not over 4 times the wall thickness.

Where

S_o = Cross section of the specimen

(ii), (iii) and (iv) * * *

(3) * * *

AUG 25 2004

(4) Cracks Examination. All cylinders must be examined in accordance with ISO 9809-2:1999 or inspected by the wet magnetic particle method in accordance with ASTM E-709-85 before closing in and after heat treatment to detect the presence of quench cracks or other discontinuities.

§ 178.37(1) *Acceptable results of production tests and inspections.*

(1) Impact tests. The Charpy V-notch impact properties for the three specimens for each lot of cylinders must not be less than the values shown below at -50°C:

<u>Size (mm)</u>	<u>Average value for acceptance 3 specimens</u>	<u>Minimum value 1 specimen only of the three</u>	<u>Lateral expansion millimeter</u>	<u>Percent fibrous fracture</u>
10x4	53 J/cm ² (12.0 ft.lbs.)	44 J/cm ² (10.0 ft.lbs)	0.305	50

(2) Flattening Test. Flattening required without cracking to eight times the wall thickness of the tested cylinder. Continue flattening until cracking occurs. Maximum degree of flattening attained without cracking and knife clearance must be entered on the inspector's report.

(3) Flawed Burst Test. The failure must originate in the cylinder sidewall and be by leakage before burst.

(4) Mechanical Tests.

(i) Tensile strength must not exceed 159,000 psi.

(ii) Elongation must be at least 14 percent of 5.65 times S₀, with width not over 4 times the wall thickness. The elongation must meet the requirement of ISO 9809-2:1999.

(5) Cracks Examination. Any cylinder found to have a quenching crack must be rejected and may not be requalified.

(6) Hardness Measurement. The tensile strength equivalent of the hardness number obtained may not be more than 159,000 psi; (HRC 34(Brinell 334)). When the results of a hardness test exceeds the maximum permitted, two or more retests may be made: however, the hardness number obtained in each retest may not exceed the maximum permitted.

§ 178.37(m) *Leakage test and ultrasonic examination.*

(1) Leakage test is not required.

(2) After heat treatment, each cylinder must be inspected by the ultrasonic examination method of ISO 9809-2:1999 to detect the presence of quench cracks or other discontinuities.

§ 178.37(n) *Rejected cylinders from production testing.*

(1) Reheat treatment of cylinders rejected by the impact test is authorized; subsequent thereto, acceptable cylinders must pass all prescribed tests.

(2) Reheat treatment of cylinders rejected by the flattening test is authorized; subsequent thereto, acceptable cylinders must pass all prescribed tests.

(3) Reheat treatment of cylinders rejected by the flawed burst test is authorized; subsequent thereto, acceptable cylinders must pass all prescribed tests.

(4) Reheat treatment of cylinders rejected by the mechanical properties test is authorized; subsequent thereto, acceptable cylinders must pass all prescribed tests.

(5) Cylinders rejected by the magnetic particle or ultrasonic examination (wherein the defects are not quench cracks) may be reheat treated, subsequent thereto, acceptable cylinders must pass all prescribed tests.

(6) Reheat treatment of cylinders rejected by the hardness measurement is authorized; subsequent thereto, acceptable cylinders must pass all prescribed tests.

AUG 25 2004

b. TESTING -

(1) Five year requalification - Each cylinder must be requalified for use every five years in accordance with § 180.209 as prescribed for DOT-3AA cylinders or by ultrasonic examination. Cylinders requalified after having been subjected to the action of fire, must be reported to OHMEA prior to being placed back in service.

(i) Hydrostatic pressure test - Each cylinder must be tested in accordance with § 180.205(g) except

(A) Each cylinder must be tested to at least $3/2$ times the marked service pressure.

(B) A rejection elastic expansion (REE) limit must be developed as specified in CGA Pamphlet C-5.

(ii) Ultrasonic Examination - As an alternative, each cylinder may be requalified by ultrasonic examination (UE) in accordance with an approved DOT exemption and a retest facility that is authorized for UE of high strength (tensile strength equal or greater than 159,000 psi) cylinders.

(A) The retest results for the ultrasonic examination must be submitted to OHMEA annually.

(B) A cylinder that has been exposed to fire or to excessive heat (temperatures of 1000°F or greater) may not be retested by ultrasonic examination.

(2) Ten years requalification - Cylinders made under this exemption may be requalified every ten years if they are requalified in accordance with an approved DOT exemption and a retest facility that is authorized for UE of high strength (tensile strength equal or greater than 159,000 psi) cylinders provided each cylinder meets all of the following:

(i) The cylinder is used exclusively for argon, helium, krypton, neon, nitrogen, oxygen, xenon, permitted mixtures of these gases in accordance with § 173.301a(a)(1) that contain less than 13 percent carbon monoxide, a dew point of below minus 52° F at 1 atmosphere.

(ii) The cylinder is hammer tested in accordance with CGA pamphlet C-6.

(iii) The cylinder is not used for underwater breathing.

(iv) Each cylinder is stamped with five-point star as described in § 180.209(b)(vi) immediately following the UE.

8. SPECIAL PROVISIONS:

a. The manufacturer of the cylinder covered by this exemption must retain the test reports required by this exemption indefinitely as long as the cylinders are authorized for use.

b. A copy of the Inspector's report for each of the first three lots produced must be submitted to the OHMEA prior to shipment.

c. A person who is not a holder of this exemption, but receives a package covered by this exemption, may use the packaging authorized by this exemption for the transportation of hazardous materials specified in paragraph 6, only in conformance with the terms of this exemption.

d. Each packaging manufactured under the authority of this exemption must be marked with a registration symbol designated by the Office of Hazardous Materials Exemptions and Approvals Program for a specific manufacturing facility.

e. A current copy of this exemption must be maintained at each manufacturing facility at which this packaging is manufactured and must be made available to a DOT representative upon request.

AUG 25 2004

f. In accordance with the provisions of Paragraph (b) of § 173.22a, persons may use the packaging authorized by this exemption for the transportation of the hazardous materials specified in paragraph 6, only in conformance with the terms of this exemption.

g. A current copy of this exemption must be maintained at each facility where the package is offered or reoffered for transportation.

h. These cylinders may not be used for carriage of any gas that would cause hydrogen embrittlement of the steel.

i. Filling limits specified in § 173.302a(b) are not authorized. Under no circumstance are these cylinders to be filled to a pressure exceeding the marked service pressure at 21°C (70°F).

j. Transportation of oxygen by aircraft is only authorized when in accordance with § 172.102(c)(2), Special Provision A52 and § 175.85(h) and (i).

9. MODES OF TRANSPORTATION AUTHORIZED: Motor vehicle, rail freight, and cargo aircraft only (see restriction in paragraph 8(j) above).
10. MODAL REQUIREMENTS: A current copy of this exemption must be carried aboard each aircraft used to transport packages covered by this exemption. The shipper must furnish a copy of this exemption to the air carrier before or at the time the shipment is tendered.
11. COMPLIANCE: Failure by a person to comply with any of the following may result in suspension or revocation of this exemption and penalties prescribed by the Federal hazardous materials transportation law, 49 U.S.C. 5101 et seq:
- o All terms and conditions prescribed in this exemption and the Hazardous Materials Regulations, 49 CFR Parts 171-180.
 - o Persons operating under the terms of this exemption must comply with the security plan requirement in Subpart I of Part 172 of the HMR, when applicable.
 - o Registration required by § 107.601 et seq., when applicable.

AUG 25 2004

Each "Hazmat employee", as defined in § 171.8, who performs a function subject to this exemption must receive training on the requirements and conditions of this exemption in addition to the training required by §§ 172.700 through 172.704.

No person may use or apply this exemption, including display of its number, when this exemption has expired or is otherwise no longer in effect.

- 12. REPORTING REQUIREMENTS: The carrier is required to report any incident involving loss of packaging contents or packaging failure to the Associate Administrator for Hazardous Materials Safety (AAHMS) as soon as practicable. (Sections 171.15 and 171.16 apply to any activity undertaken under the authority of this exemption.) In addition, the holder(s) of this exemption must inform the AAHMS, in writing, of any incident involving the package and shipments made under the terms of this exemption.

Issued in Washington, D.C.:

for 

 Robert A. McGuire
 Associate Administrator for
 Hazardous Materials Safety

AUG 25 2004

(DATE)

Address all inquiries to: Associate Administrator for Hazardous Materials Safety, Research and Special Programs Administration, Department of Transportation, Washington, D.C. 20590. Attention: DHM-31.

Copies of this exemption may be obtained by accessing the Hazardous Materials Safety Homepage at <http://hazmat.dot.gov/exemptions> Photo reproductions and legible reductions of this exemption are permitted. Any alteration of this exemption is prohibited.

PO: Toughiry/ss