

June 23, 2006



U.S. Department  
of Transportation

400 Seventh Street, S.W.  
Washington, D.C. 20590

**Pipeline and Hazardous  
Materials Safety Administration**

DOT-SP 6517  
(TENTH REVISION)

EXPIRATION DATE: May 31, 2010

(FOR RENEWAL, SEE 49 CFR § 107.109)

1. GRANTEE: Taylor-Wharton  
Huntsville, AL
2. PURPOSE AND LIMITATIONS:
  - a. This special permit authorizes the manufacture, mark, sale and use of non-DOT specification welded steel cylinders conforming with all regulations applicable to a DOT Specification 4BW, except as specified herein, for the transportation in commerce of acetylene. This special permit provides no relief from the Hazardous Materials Regulations (HMR) other than as specifically stated herein.
  - b. The safety analyses performed in development of this special permit only considered the hazards and risks associated with transportation in commerce.
3. REGULATORY SYSTEM AFFECTED: 49 CFR Parts 106, 107 and 171-180.
4. REGULATIONS FROM WHICH EXEMPTED: 49 CFR §§ 173.303(a), 174.3, and 176.3 in that non-DOT specification cylinders are not authorized, except as specified herein.
5. BASIS: This special permit is based on the application of Taylor-Wharton dated June 13, 2006, submitted in accordance with § 107.109 and supplement information dated June 21, 2006.

6. HAZARDOUS MATERIALS (49 CFR § 172.101):

Proper Shipping Name/ Hazardous Material Description	Hazard Class/ Division	Identi- fication Number	Packing Group
Acetylene, dissolved	2.1	UN1001	N/A

7. SAFETY CONTROL MEASURES: Prescribed packagings are non-DOT specification steel cylinders which are in conformance with DOT Specification 4BW (§§ 178.35 and 178.61) except as follows:

a. Each cylinder must comply with §§ 178.35(b) and 178.35(e) except that paragraph 178.35(b)(1) does not apply. Each cylinder must also comply with §§ 178.60(g)(2), 178.60(p) and 178.60(q). Cylinders must have a service pressure of 250 psig. Heads concave to pressure must have a minimum thickness equal to required thickness of the sidewall. Heads convex to pressure must have a minimum thickness equal to 2.5 times the required thickness of the sidewall. A round out pressure must be applied prior to the official test prescribed in § 178.61(i). Test pressure must be at least three times the service pressure and the minimum burst pressure must be six times the service pressure. Cylinders having outside diameters greater than 5 inches must have a minimum wall thickness of 0.087 inch. The wall stress must be calculated by the formula described in § 178.61(f)(4):

$$S = 3P(1.3D^2 + 0.4d^2) / [E(D^2 - d^2)]$$

b. Cylinders may not be identified as DOT-4BW and, instead, each one must be marked "DOT-SP 6517." The applicable portion of the inspector's report must be so noted.

c. Only those cylinders that comply with the specifications, calculations, and test data submitted by the petitioner in support of the petition dated May 18, 1971, and as further provided herein, including the 12-inch diameter cylinder, are qualified under the terms of this special permit. Tests to qualify cylinders of

any new design that differs from the above (e.g., change in diameter, length, volume, ends, etc.) must satisfy the following, and the results thereof must be submitted to the Office of Hazardous Materials Special Permit and Approvals (OHMSPA):

- (1) Cycle test data, 20,000 cycles.
- (2) Permanent deformation measurements on heads convex to pressure as a result of cycle tests.
- (3) Burst tests.
- (4) Hydrostatic test result comparison to existing cylinder models.
- (5) Drawings.

d. No new construction authorized after July 15, 1978.

8. SPECIAL PROVISIONS:

a. In accordance with the provisions of Paragraph (b) of § 173.22a, persons may use the packaging authorized by this special permit for the transportation of the hazardous materials specified in paragraph 6, only in conformance with the terms of this special permit.

b. A person who is not a holder of this special permit, but receives a package covered by this special permit, may reoffer it for transportation provided no modification or change is made to the package and it is offered for transportation in conformance with this special permit and the HMR.

c. A current copy of this special permit must be maintained at each facility where the package is offered or reoffered for transportation.

d. Each packaging manufactured under the authority of this special permit must be marked with a registration symbol designated by the Office of Hazardous Materials Special Permits and Approvals for a specific manufacturing facility.

e. Packages specified herein marked "SP-6517" prior to November 24, 1976, may be transported under the terms of this special permit.

f. Packagings permanently marked 'DOT-E 6517', prior to October 1, 2007 may continue to be used under this special permit for the remaining service life of the packaging or until the special permit is no longer valid. Packagings marked on or after October 1, 2007 must be marked 'DOT-SP 6517'.

g. Shipping papers displaying 'DOT-E 6517' may continue to be used until October 1, 2007, provided the special permit remains valid.

9. MODES OF TRANSPORTATION AUTHORIZED: Motor vehicle, rail freight, cargo vessel.
10. MODAL REQUIREMENTS: A current copy of this special permit must be carried aboard each cargo vessel used to transport packages covered by this special permit.
11. COMPLIANCE: Failure by a person to comply with any of the following may result in suspension or revocation of this special permit and penalties prescribed by the Federal hazardous materials transportation law, 49 U.S.C. 5101 et seq:
  - o All terms and conditions prescribed in this special permit and the Hazardous Materials Regulations, Parts 171-180.
  - o Persons operating under the terms of this special permit must comply with the security plan requirement in Subpart I of Part 172 of the HMR, when applicable.
  - o Registration required by § 107.601 et seq., when applicable.

Each "Hazmat employee", as defined in § 171.8, who performs a function subject to this special permit must receive training on the requirements and conditions of this special permit in addition to the training required by §§ 172.700 through 172.704.

No person may use or apply this special permit, including display of its number, when the special permit has expired or is otherwise no longer in effect.

Under Title VII of the Safe, Accountable, Flexible, Efficient Transportation Equity Act: A Legacy for Users (SAFETEA-LU)- 'The Hazardous Materials Safety and Security Reauthorization Act of 2005' (Pub. L. 109-59), 119 Stat. 1144 (August 10, 2005), amended the Federal hazardous materials transportation law by changing the term 'exemption' to 'special permit' and authorizes a special permit to be granted up to two years for new special permits and up to four years for renewals.

12. REPORTING REQUIREMENTS: Shipments or operations conducted under this special permit are subject to the Hazardous Materials Incident Reporting requirements specified in 49 CFR §§ 171.15 - Immediate notice of certain hazardous materials incidents, and 171.16 - Detailed hazardous materials incident reports. In addition, the grantee(s) of this special permit must notify the Associate Administrator for Hazardous Materials Safety, in writing, of any incident involving a package, shipment or operation conducted under terms of this special permit.

Issued in Washington, D.C.:



for Robert A. McGuire  
Associate Administrator  
for Hazardous Materials Safety

Address all inquiries to: Associate Administrator for Hazardous Materials Safety, Pipeline and Hazardous Materials Safety Administration, Department of Transportation, Washington, D.C. 20590. Attention: PHH-31.

Copies of this special permit may be obtained by accessing the Hazardous Materials Safety Homepage at [http://hazmat.dot.gov/sp\\_app/special\\_permits/spec\\_perm\\_index.htm](http://hazmat.dot.gov/sp_app/special_permits/spec_perm_index.htm) Photo reproductions and legible reductions of this special permit are permitted. Any alteration of this special permit is prohibited.

PO: KFW/sln